





## Producer III and Producer IIIN Specifications

 **Notes:**

- For printer specifications, refer to your Printer User Guide.
- For minimum and optimum PC requirements for the Producer 6100, refer to the *Additional 6100 Specifications* section on page 6.

	Producer III			Producer IIIN		
	6100	7100	8100	6100N	7100N	8100N
<b>Standard system</b>	Producer 6100, 7100, or 8100, Everest or Prism printer, Rimage Producer Software Suite (PSS), and external PC (7100 and 8100 only).  <b>Note:</b> For minimum and optimum PC requirements for the Producer 6100, refer to the <i>Additional 6100 Specifications</i> section on page 6.			Producer 6100N, 7100N, or 8100N, Everest or Prism printer, and Rimage Producer Software Suite (PSS).		
<b>Number of recorders</b>	1	2	4	1	2	4
<b>Physical size</b>						
<b>Height*</b>	23.25 in (58.7 cm)	25.25 in (64.1 cm)	28.75 in (72.7 cm)	23.25 in (58.7 cm)	25.25 in (64.1 cm)	28.75 in (72.7 cm)
<b>Width</b>	16.25 in (41.3 cm)	16.25 in (41.0 cm)	16.5 in (41.9 cm)	16.25 in (41.3 cm)	16.25 in (41.0 cm)	16.5 in (41.9 cm)
<b>Depth**</b>	24.75 in (62.9 cm)	24.75 in (62.9 cm)	24.75 in (62.9 cm)	24.75 in (62.9 cm)	24.75 in (62.9 cm)	24.75 in (62.9 cm)
<b>Weight</b>	64 lb (29.0 kg)	70 lb (31.8 kg)	83 lb (37.6 kg)	84 lb (38.1 kg)	90 lb (40.9 kg)	103 lb (46.7 kg)
<b>with Everest</b>	109 lb (49.4 kg)	115 lb (52.2 kg)	128 lb (58.1 kg)	129 lb (58.5 kg)	135 lb (61.2 kg)	148 lb (67.1 kg)
<b>with Prism</b>	84 lb (38.1 kg)	90 lb (40.8 kg)	103 lb (46.7 kg)	104 lb (47.2 kg)	110 lb (49.9 kg)	123 lb (55.8 kg)
	* Height does not include the optional status light. The status light is 6 in (15.2 cm) high.					
	** Leave an additional 3.5 in (9 cm) for cabling.					
<b>Supported operating systems</b>	Windows XP Professional with SP2 or higher and Windows Server 2003.			The supported operating system is installed on the embedded PC. Only the installed operating system is supported on this product.		
<b>Software requirements</b>	Rimage Producer Software Suite (PSS) installed on the external PC (7100 and 8100 only).  <b>Note:</b> For minimum and optimum PC requirements for the Producer 6100, refer to the <i>Additional 6100 Specifications</i> section on page 6.			The required software is installed on the embedded PC.		

Specifications are continued on page 6.

	Producer III			Producer IIIN		
	6100	7100	8100	6100N	7100N	8100N
<b>Input bin capacity</b>	100 discs per bin. This system has 3 input bins.  <b>Note:</b> You can configure the Producer 6100, 6100N, 8100 and 8100N to have 4 input bins if you configure the external output bin as the only output bin. If you set up your system this way, user intervention is required after 75 discs for the 8100 and 8100N, and after 20 discs for the 6100 and 6100N.					
<b>Output capacity</b>	300 discs before operator intervention is required when the carousel is used as the output bin.  <b>Note:</b> The Producer 6100, 6100N, 8100 and 8100N have an external output bin. See the Input bin capacity note above for additional information.					
<b>Networking ability</b>	To submit orders from a networked PC, refer to the Rimage Advanced Setup (Networking) Guide.					
<b>Power</b>	100 – 240 VAC, 60/50 Hz, 4.7 – 3.7 Amp, 500 watt maximum					
<b>Media requirements</b>	Refer to your Printer User Guide for the correct media requirements. Rimage Media Kits™ are designed for optimum recording and print performance.					
<b>Ribbon requirements</b>	Refer to your Printer User Guide for the correct printer ribbons. Rimage Media Kits include the required print ribbons.					
<b>Label design requirements</b>	Refer to your Printer User Guide for label design requirements.					
<b>Operating temperature</b>	60° to 86° F (16° to 60° C)					
<b>Humidity</b>	40% to 80% non-condensing					
<b>Storage temperature</b>	5° to 95° F (-15° to 35° C)					

## Additional 6100 Specifications

<p><b>Minimum PC requirements for the Producer 6100</b></p> <p>If you do not understand these requirements, ask your computer technician for help or refer to your PC documentation.</p>	<p><b>Processor:</b> Celeron, 2.0 GHz  <b>RAM/Memory:</b> 1GB  <b>Fixed Storage:</b> 60 GB of free space  <b>Graphics:</b> 1024 x 768 screen resolution, 16-bit color  <b>Ports:</b> One USB 2.0 port  <b>Operating System:</b> Windows XP Professional with SP2 or Windows Server 2003.  <b>Software:</b> Rimage Producer Software Suite (PSS) version 8.1 or higher.</p>
<p><b>Optimum PC requirements for the Producer 6100</b></p> <p>These PC specifications are recommended if you are using the Rimage Producer 6100 to record DVD/BDs.</p> <p>*Throughput is based on this system configuration. For optimum performance, use a PC with these specifications.</p>	<p><b>Processor:</b> Core 2 Duo, E4300  <b>RAM/Memory:</b> 1GB, DDR2-533  <b>Fixed Storage:</b> Two 250GB, 7,200 RPM Enterprise Class Serial ATA Hard drives configured in RAID 0:</p> <ul style="list-style-type: none"> <li>• Partition one is used to house the operating system</li> <li>• Partition two is used for the Rimage System Folder</li> </ul> <p><b>Ports:</b> One USB 2.0 port  <b>Graphics:</b> 1024X768, 32-bit High Color</p>